

## KS832

Up to 8 Exchange Lines  
 Configured for up to 32 Extensions 201 – 232  
 Expandable up to 16 exchange lines and  
 128 Extensions via Slot in Cards  
 Key Phone Compatible (KP832)  
 Auto Attendant (DISA) with 30 seconds OGM  
 80 System Speed dials  
 Auto Fax Transfer in Auto-attendant  
 Transfer & Pickup  
 Caller ID compatible  
 Remote Programming  
 Operator Call  
 Hot Line  
 Broadcasting /Tannoy  
 Call Forward to Secretary and on Busy  
 External Music On-Hold Port  
 Conference Call  
 Programmable Call Restrictions & Call Barring  
 Exchange Lines 'in use' LED's  
 CE & RoHS Compliant



## Specifications

|                                    |   |
|------------------------------------|---|
| Capacity                           | CO Lines: 16      Extensions: 128   |
| Exterior Jack                      | Standard RJ11 Sockets: Line Port, Extension Port & COM Port.<br>3.5mm Audio Socket: External Music Input Port   |
| Communication                      | 17 Channels   |
| Transmission                       | Extension to Extension $\leq 1.5\text{dB}$<br>Extension to Trunk Line $\leq 2.0\text{dB}$   |
| Ring Current                       | AC65v / 50Hz  |
| Feedback current                   | DC33V/25mA  |
| Degree of Unbalance about Earth    | 300Hz---600Hz $\leq 40\text{dB}$<br>600Hz---3400Hz $\leq 46\text{dB}$   |
| Dial Mode                          | DTMF  |
| Signal Tone                        | Internal dial tone: 450Hz, Continuous sine wave<br>Internal ring-back tone: 450Hz, sine wave, 1s on / 4s off<br>Internal busy tone: 450 Hz, sine wave, 0.3s on / 0.3s off<br>Internal confirmation tone: 450 Hz, sine wave, 1s on<br>Internal error tone; 450 Hz, sine wave, 0.3s on / 0.3s off |
| Caller ID                          | Receive: DTMF, FSK (Bell 202)<br>Send: FSK (Bell 202)   |
| Power Supply                       | AC230V +/- 10%, 12w   |
| Line & Extension Socket Connection | Pins 3 and 4 of RJ11 Socket   |
| Dimensions                         | 53 x 44 x 19 cm   |